



BESTPACK'S CARTON SEALING BOPP TAPE

WITH THE RIGHT TAPE SEAL CONFIDENTLY
AND EFFECTIVELY EVERY TIME

TAPE CHARACTERISTICS	BP (ACRYLIC)	BG (ACRYLIC)	HT (HOT MELT)
Application & Storage Temperature	32°F - 150°F	32°F - 150°F	32°F - 104°F
Service Temperature	-30°F - 200°F	-30°F - 200°F	30°F - 140°F
Quick Tack		✓	✓
Usage in Extreme Temperatures (Ideal for freezer/cold & high heat temperature applications)	✓	✓	
Clarity (will not discolor over time)	✓	✓	
Consistent & Easy Release			✓
UV Light Resistant	✓	✓	
Long Shelf Life	✓	✓	
High Sheer			✓
ISO 9001 - Quality Standard	✓	✓	✓
ISO 14001 - Environmental Standard	✓	✓	✓

CARTON SEALING TAPE SIZES

BP ACRYLIC:	BP16 - 1.6 mil	BP18 - 1.8 mil	BP20 - 2.0 mil
	BP26 - 2.6 mil	BP31 - 3.1 mil	
BG ACRYLIC:	BG16 - 1.6 mil	BG18 - 1.8 mil	BG20 - 2.0 mil
HT HOTMELT:	HT16 - 1.6 mil	HT18 - 1.8 mil	HT30 - 3.0 mil

