



\*Model Shown: PP-6030 + PP-6040M

## 6030 SERIES

# SEMI-AUTOMATIC POLY BUNDLING SLEEVE WRAPPING MACHINE

Traditional poly bundlers with “Bull’s Eyes”

TEMPERATURE:  
**0-400°F**

POWER:  
**15 KW**

FLOW:  
**Top Down**

WARRANTY:  
**1 Year**



Specifications based on PP-6030 + PP-6040M

Meet BPX Solutions Semi-Automatic Polybundler & Shrink Tunnel Combo. The perfect solution for bundling beverages together.

#### AVAILABLE MODELS:

- PP-6030 + PP-6040M
- PP-6030

# SEMI-AUTOMATIC POLY BUNDLERS

## STANDARD FEATURES INCLUDE:

- Pusher arm advances product into seal area.
- Easy to use front control panel with digital temperature controls
- Dual film rack with independent Heavy Duty motor drive
- Pneumatic product hold down to stabilize product on discharge conveyor
- Good air circulation inside of tunnel chamber for best shrink results
- Machine speeds of 5 to 10 PPM depending on product size and film gauge used.
- Heavy duty high RPM, high air velocity blower motor
- Heavy duty dead roller rod conveyor
- Cooling fan on discharge end of tunnel
- Emergency stop switch
- Heavy duty leveling pads
- Air regulator with water trap

## POPULAR SEMI-AUTOMATIC POLY BUNDLER MODELS

MODELS	SEAL BAR WIDTH	MAX FILM WIDTH	MAX PACKAGE SIZE (LENGTH X WIDTH X HEIGHT)	TUNNEL DIMENSIONS (LENGTH X WIDTH X LENGTH)	POWER REQUIREMENTS
PP-6030 + PP-6040M	(27.5")	(25.0")	(12.0" x 12.0" x 12.0")	(59.0" x 23.5" x 16.0")	220 Volt, 3 Phase 66 AMPS
PP-6030 (Sealer Only)	(27.5")	(25.0")	(12.0" x 12.0" x 12.0")	-	220 Volt, 3 Phase 66 AMPS

Information subject to change without notice.