



*Model Shown: PP-5030LH-220

5030 SERIES

HIGH SPEED SHRINK TUNNELS

Shrink Tunnels Designed Around Your Speed and Size Needs

CHAMBER
LENGTH:
(79.0")

OVERALL
LENGTH:
(93.0")

CHAMBER SIZE:
(L X W)
(20.0" x 12.0")

POWER
REQUIREMENTS:
220 Volts 52 Amps 3 Phase



Specifications based on SM-5030LH-220

High-speed heat shrink tunnels are built to keep up with the demands of fast-paced production lines without sacrificing quality. These tunnels deliver precise, consistent heat to ensure a flawless, secure seal, even at high speeds. Ideal for industries where efficiency is paramount, high-speed shrink tunnels can handle high-volume packaging with various materials and product sizes, enhancing productivity and reducing downtime. Perfect for everything from retail-ready multipacks to heavy-duty shipping requirements, they help streamline operations while delivering professional, durable packaging.

AVAILABLE MODELS:

- PP-5030XL
- PP-5030LH

HIGH SPEED SHRINK TUNNELS

STANDARD FEATURES INCLUDED:

- Live Roller Rod Conveyor with Variable Air Velocity Control
- Digital Temperature Control with Fully Re-Circulating Air Chamber
- 1 HP High Velocity Blower Motor
- Variable Air Velocity Controlled Through an Inverter
- Four Directional Air Flow, Fully Recirculating Air Chamber
- Omron Solid State Digital Temperature Control 0-400 F
- Sealed Bearings on Drive And Idler Shafts
- Live Roller Rod Conveyor
- 16 KW Heater Banks
- Heavy Duty Rollers in Tunnel Conveyor
- Automatic Tunnel Cool Down with Shut Off
- Thermal Overload Protection on Motors
- Heavy Duty Locking Casters with Leveling Bolts
- Lighted Viewing Window
- Powder Coated Painted frame

POPULAR HIGH SPEED SHRINK TUNNEL MODELS

MODELS	CHAMBER LENGTH	OVERALL LENGTH	CHAMBER SIZE	POWER REQUIREMENTS
PP-5030XL-220	(60.0")	(74.0")	(20.0" x 12.0")	42 Amps 16 kw 220 Volts 3 Phase
PP-5030LH-220	(79.0")	(93.0")		52 Amps 20 kw 220 Volts 3 Phase

Information subject to change without notice.