

AS-S Series Comparison Chart



Model	Machine Dimensions Length x Width x Height	Carton Range** Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.***	Shipping Weight (lbs.)
AS 12-2 S 2" Tape Head	(70.2**) x (26.5") x (68.0")	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 12-3 S 3" Tape Head	(70.2**) x (26.5") x (68.0**)	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 22-2 S 2" Tape Head	(77.7**) x (33.8") x (69.0")	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616
AS 22-3 S 3" Tape Head	(77.7**) x (33.8") x (69.0**)	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616

Information subject to change without notice.

U - Unlimited
All Models available in High Speed
* Safety Gates are an additional 20" Long
** Outside Dimensions Only
*** Based on a 12" long carton