

RQ Series

Random Quad Drive Carton Sealer

The BestPack RQ Series is a Semi-Automatic Random Tape Carton Sealer built for speed and rugged dependability. With a quad-belt drive, the RQ is a heavy-duty work horse that effectively seals unstable cartons, including cartons that are taller than they are long, overfilled, very heavy, or otherwise difficult to seal.

Our RQ line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Random Cartons



Top & Bottom Seal

Features

- Handles Random Carton Sizes
- Adjustable Bed Height from RQ22, RQ23, & RQ33: 20.5" - 30"
RQ44: 24.5" - 30"
- 4 Belt Drive - 2 Top and 2 Side Belts
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Height Sensor
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Interlock Safety Gates
- Low Tape or No Tape Sensor
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Random Side Compression Rollers

Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 15 Cartons/min.
Speed

90 - 100 PSI
6 - 8 SCFM
Air Requirements

535-735 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RQ22-2 2" Tape Head	(42.8") x (34.6") x (57.5")	(7.0" - U) x (7.5" - 21.0") x (4.5" - 20.0")	(20.5" - 30.0")	Up to 15	535
RQ22-3 3" Tape Head	(42.8") x (34.6") x (57.5")	(7.0" - U) x (7.5" - 21.0") x (4.5" - 20.0")	(20.5" - 30.0")	Up to 15	535
RQ23-2 2" Tape Head	(42.8") x (34.6") x (76.0")	(7.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30.0")	Up to 13	575
RQ23-3 3" Tape Head	(42.8") x (34.6") x (76.0")	(7.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30.0")	Up to 13	575
RQ EC 33-3 3" Tape Head	(42.8") x (45.0") x (76.0")	(7.0" - U) x (7.5" - 30.0") x (4.5" - 30.0")	(20.5" - 30.0")	Up to 13	600
RQ33-3-CP** 3" Tape Head	(42.8") x (45.0") x (76.0")	(7.0" - U) x (7.5" - 30.0") x (6.0" - 30.0")	(20.5" - 30.0")	Up to 13	635
RQ44-3** 3" Tape Head	(42.8") x (54.7") x (86.0")	(7.0" - U) x (7.5" - 40.0") x (6.0" - 40.0")	(24.5" - 30.0")	Up to 12	735

Information subject to change without notice.

U - Unlimited
* Outside dimensions only
** Includes Random Top Side Compression Rollers & Interlock Safety Gates
High Speed Option Available