

HT25

2.5 mil (64 micron) total tape thickness
40 micron cast BOPP low elongation film
Hot Melt Adhesive

BestPackTM
the total tape sealing solution

Overview:

HT25 is a heavy duty grade carton sealing tape for those applications needing a strong and sturdy seal.

About Our Product:

- 40 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 24 micron Hot Melt Adhesive
- Available in Hand & Machine Length Rolls
- Specially formulated 140% elongation low stretch cast film increasing Machine Length Roll performance
- RoHS Compliant
- Tape Manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.



Product Specifications:

Adhesive Type:	Hot Melt	Test Method:
Total Thickness:	2.5 mil (64 micron)	ASTM D-3652
Film Thickness:	1.6 mil (40 micron)	ASTM D-3652
Adhesive Thickness:	0.9 mil (24 micron)	ASTM D-3652
Tensile Strength:	26 lbs/inch width	ASTM D-3759
Peel Adhesion:	57 oz/inch width	ASTM D-3330
Elongation % at Break:	140%	ASTM D-3759

Service Temperature:

Min. Service Temp.: **30°F**
Max. Service Temp.: **140°F**

Usage & Storage Temperature:

Min. Usage & Storage Temp.: **32°F**
Max. Usage & Storage Temp.: **104°F**

Ideal Storage Temperature:

Ideal Storage Temp.: **77°F +/- 5°F**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.

Available Colors:



Available Lengths:

50m
100m
150m
914m

Available Widths:

48mm
72mm
96mm
144mm
288mm