

# HT30

3.0 mil (76 micron) total tape thickness  
50 micron cast BOPP low elongation film  
Hot Melt Adhesive

**BestPack**<sup>TM</sup>  
the total tape sealing solution

## Overview:

HT30 is a heavy duty grade carton sealing tape for those applications needing a strong and sturdy seal.

## About Our Product:

- 50 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 26 micron Hot Melt Adhesive
- Available in Hand & Machine Length Rolls
- Specially formulated 140% elongation low stretch cast film increasing Machine Length Roll performance
- RoHS Compliant
- Tape Manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.



## Product Specifications:

Adhesive Type:	Hot Melt	Test Method:
Total Thickness:	<b>3.0 mil (76 micron)</b>	<b>ASTM D-3652</b>
Film Thickness:	<b>2.0 mil (50 micron)</b>	<b>ASTM D-3652</b>
Adhesive Thickness:	<b>1.0 mil (26 micron)</b>	<b>ASTM D-3652</b>
Tensile Strength:	<b>33 lbs/inch width</b>	<b>ASTM D-3759</b>
Peel Adhesion:	<b>60 oz/inch width</b>	<b>ASTM D-3330</b>
Elongation % at Break:	<b>140%</b>	<b>ASTM D-3759</b>

### Service Temperature:

Min. Service Temp.: **30°F**  
Max. Service Temp.: **140°F**

### Usage & Storage Temperature:

Min. Usage & Storage Temp.: **32°F**  
Max. Usage & Storage Temp.: **104°F**

### Ideal Storage Temperature:

Ideal Storage Temp.: **77°F +/- 5°F**  
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.

### Available Colors:



### Available Lengths:

<b>50m</b>
<b>100m</b>
<b>150m</b>
<b>914m</b>

### Available Widths:

<b>48mm</b>
<b>72mm</b>
<b>96mm</b>
<b>144mm</b>
<b>288mm</b>